






ADVANTAGES/USES	CURE & SEAL WB	CURE & SEAL WB 1315	CONCRETE & MASONRY SEALER WB	SALT BARRIER WB	CURE & HARDEN
	 <ul style="list-style-type: none"> • Low VOC, water based mix • Tack-free in 2-4 hours • Ready to use (no diluting) • Sprays white, dries clear • Interior or exterior application • new or existing applications • Concrete, masonry, terrazzo, brick, stone, masonry, and other cementitious materials • Seal many types of resilient floor coverings and prous tile • Commercial and residential applications 	 <ul style="list-style-type: none"> • Meets ASTM C1315 type 1 Class A • Low VOC, water-based mix • Tack-free in 2-4 hours • Ready to use • Sprays white, dries clear • Interior or exterior applications • Concrete, masonry, terrazzo, brick, stone, masonry, and other cementitious materials. • Decorative concrete • Commercial and residential applications 	 <ul style="list-style-type: none"> • Protects and seals • Repels water • Non-staining, colorless, non-yellowing • Ready to use • Breathable, does not trap moisture • Protects from effects of rain and other water penetration, chemicals, deicing salts, freeze-thaw, and smog • Exterior above-grade applications • Concrete, brick masonry, stucco, burnished or split-faced block, natural and synthetic stone, stucco, and other cementitious materials 	 <ul style="list-style-type: none"> • Non-gloss finish that won't change the surface appearance • Non-staining, non yellowing, dries tack-free • Ready to use • Waterbased formula provides breathable, deep penetrating protection that does not trap moisture • Repels water and protects from salt deterioration • Reduces efflorescence • Excellent for driveways and garages prone to salt damage from vehicle traffic 	 <ul style="list-style-type: none"> • Sodium silicate • Harden concrete surfaces • Improves abrasion resistance • Extends concrete service life • Aids in curing of newly finished concrete • Minimizes shrinkage cracking • Non-staining, non-yellowing • Ready to use • Water based, 0g/L VOC • Will not inhibit adhesion of secondary coatings or adhesives
APPLICATION					
Finish Type	Satin	High Gloss	Natural Finish	Natural Finish	Natural Finish
VOC	<100 g/L	<150 g/L	211 g/L	211 g/L	0 g/L
Dry Time	1-2 hours (touch) 4-12 hours (traffic) at 70°F	1-2 hours (touch) 4-12 hours (traffic) at 70°F	2-4 hours at 70°F(21°C)	2-4 hours at 70°F	60-120 minutes
Coverage Rate	Curing: Broomed or Troweled - 200-300 Sq. Ft./Gal. Second Coat 300-500 Sq. Ft./Gal.	Curing: Broomed or Troweled - 200-300 Sq. Ft./Gal. Second Coat 300-500 Sq. Ft./Gal.	125 Sq. Ft. / gal, per coat	125-300 Sq. Ft. / gal, per coat	150-800 Sq. Ft. per gal.
Sizes Available	1 gal. bottle, 5 gal. pail, 55 gal. drum	1 gal. bottle, 5 gal. pail, 55 gal. drum	1 gal. bottle, 5 gal. pail, 55 gal. drum	1 gal. bottle, 5 gal. pail, 55 gal. drum	5 gal. pail, 55 gal. drum