

Benefits of Tenon® Concrete Repair Products

- Quicker return to service
- High strength for ultimate performance
- Easily mix with water for ease of use
- Engineered for optimal balance of performance and protection



Tenon® offers a wide variety of fast-setting, high-performing professional concrete patching and resurfacing products



Tenon® offers multiple high-performance repair options for commercial pavement repair including Commercial DOT Repair and Critical Pavement Repair

Also check out our Tenon® Set Retarder and SuperFlow!



SPEC BLENDED CONSTRUCTION PRODUCTS®

info@tccmaterials.com
www.tccmaterials.com
Rev. 01/24



WWW.TENONSOLUTIONS.COM

CONCRETE REPAIR & RESTORATION

RAPID PATCH® 100



- High early strength
- Fiber enhanced for improved impact resistance
- Suitable for DOT horizontal concrete repairs
- Integral Corrosion Inhibitor

SET TIME	37 minutes
MINIMUM DEPTH	½ inch
MAXIMUM LIFT	Full depth
YIELD RATE	0.40 cu. ft. (50 lb)

RAPID PATCH® 200



- High-strength, fast setting, low shrinkage
- Fiber enhanced for extreme flexural strength
- High bond strength
- Integral Corrosion Inhibitor

SET TIME	18 minutes
MINIMUM DEPTH	½ inch
MAXIMUM LIFT	2 inches
YIELD RATE	0.40 cu. ft. (50 lb)

VERTICAL REPAIR CI



- Non-slumping, high strength non-shrink
- Can be shaved or molded
- Excellent for patching honeycombs and repairs on masonry and stucco
- High compressive and flexural strength for long term durability

SET TIME	15 minutes
MINIMUM DEPTH	¼ inch
MAXIMUM LIFT	2 inches
YIELD RATE	0.46 cu. ft. (50 lb)

COMMERCIAL DOT REPAIR



- High-strength, fast setting, low shrinkage
- For concrete repair and overlays
- Suitable for DOT horizontal concrete repairs
- Integral corrosion inhibitor

SET TIME	22 minutes
MINIMUM DEPTH	2 inches
MAXIMUM LIFT	8 inches
YIELD RATE	0.40 cu. ft. (50 lb)

COMMERCIAL DOT REPAIR EXTENDED



- High-strength, fast setting, low shrinkage
- Pre-extended for ease of use
- Suitable for DOT horizontal concrete repairs
- Integral Corrosion Inhibitor

POT LIFE @ 70°F	1-1 ½ hrs
VOC CONTENT	<11 g/L
APPLICATION THICKNESS	30 wet mils (16 mils dry)

CRITICAL PAVEMENT REPAIR (CPR)



- Ultra-high early strength
- Polymer modified for extreme bond strength
- Fiber reinforced for high flexural strength and excellent ductility
- Integral corrosion inhibitor

SET TIME	20 minutes
MINIMUM DEPTH	½ inch
MAXIMUM LIFT	4 inches
YIELD RATE	0.45 cu. ft. (50 lb)

SELF-LEVELING RESURFACER



- Cement based for interior or exterior use
- Designed as an underlayment or wear surface
- Accepts foot traffic in as little as 6 hours

SET TIME	75 minutes
MINIMUM DEPTH	Featheredge
MAXIMUM LIFT	1 inch
YIELD RATE	6-44 sq. ft. (50 lb)



Tenon® Self-Leveling Resurfacer is designed to correct damaged finishes prior to installation of finished flooring or as a wear surfacer for light industrial applications



Tenon® Vertical Repair CI is a non-slumping, high-performing, moldable patching material for correcting blemishes in vertical and overhead industrial applications