



TENON[®]

Concrete & Masonry Dissolver



Ready to Use

Tenon[®] Concrete & Masonry Dissolver is an environmentally friendly liquid alternative to aggressive acid concrete removers. Concrete & Masonry Dissolver can be used to safely remove cured concrete, mortar, grout, and stucco build-up from tools, concrete forms, job mixers, hardware, shoring, and more. This product deconstructs the bond between the Portland cement component, turning it into a soft paste-like consistency that is easily removed from the surface.

Features:

- Saves time & money; efficiently cleans unwanted concrete from surfaces without scraping, chiseling, or acid washing
- Begins to work immediately upon application
- 100% biodegradable
- Non-toxic to plants & vegetation
- Does not contain any harmful acids
- Non-corrosive & non-fuming



Application

- Apply to dry surfaces only; water will neutralize and stop the chemical process.
- Spray to completely saturate unwanted hardened concrete on trucks, tools, and equipment, or submerge and soak in a tray. Do not allow the product to evaporate or dry on surfaces or it will need to be reapplied.
- Product will begin to foam upon contact with dried cement, turning white on contact. It will then darken and soften.
- Allow the product to penetrate 10 - 15 minutes, then reapply to the same area if needed. The thickness of the concrete will determine whether a second application is needed.
- Magnesium tools should not be saturated for more than 30 minutes as darkening may occur.
- Do not rinse until the concrete has begun to soften and release from the surface, usually within 20 - 35 minutes. Once material is softened, a stiff nylon brush and water is helpful to remove product. Rinse with cold water, a garden hose with pressure nozzle, or pressure washer.
- For thick build-up, repeat cleaning instructions until build-up has softened. Mechanical means and multiple applications may be necessary for removing very thick areas.

Available In:

Tenon® Concrete & Masonry Dissolver is available in a 28 oz. (0.83 L) bottle, 1 gal. (3.78 L) bottle, 5 gal. (18.93 L) pail, 55 gal. (208 L) drum, and 275 (1040 L) gal. tote upon request.



28 oz.

BOM #121006



1 Gal.

BOM #120911



5 Gal.

BOM #120912



55 Gal.

BOM #121105

For professional use only.

It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use. For technical assistance, please contact TCC Materials. To acquire technical and safety literature, please visit our website.