



TENON[®]

X-Tender



Minimize Rapid Moisture Loss

Tenon® X-Tender is a VOC-compliant concentrate (mixed 1 part concentrate to 9 parts water) that creates a sprayable monomolecular polymer film when properly sprayed to freshly placed concrete. X-Tender is specifically designed to minimize rapid moisture loss from concrete surfaces prior to curing.

Features:

- Significantly reduces plastic shrinkage and cracking caused by evaporation in low humidity, high temperature, and high wind applications
- Compatible with concrete cures, sealers, and toppings
- Minimizes wind crusting
- Increases productivity
- Water based, no odor
- VOC compliant
- 9:1 water to X-Tender mix ratio



Application

Apply with a low-pressure sprayer that produces a flowrate of 0.5 gallons per minute. Apply the 9:1 water to X-Tender diluted solution immediately after screeding and/or between finishing operations as needed. The fugitive pigment will disappear completely upon drying. Do not allow pooling or puddling. If pooling or puddling occurs, wipe up immediately and rinse with water.

Coverage Rate

After dilution: 200-400 sq. ft. / gal. (4.9-9.8 sq. m. / L)

Product Details

Color	Light Orange
Freezing Point	32° F (0° C)
VOC	<50 gal. / L

Available In:

Tenon® X-Tender is available in a 1 gal. pail (3.78 L) and a 5 gal. pail (18.93 L).



5 Gal.
BOM #114872



1 Gal.
BOM #114871

For professional use only.

It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use. For technical assistance, please contact TCC Materials. To acquire technical and safety literature, please visit our website.