

Adhesive Base Coat PM



Adhesive Base Coat PM

Adhesive and base coat requiring only water for mixing



ER: INJURIOUS TO EYES, CAUSES SI



Excellent workability, smooth, & easy

50 lb. (22.67 ka)

Tenon® Adhesive Base Coat PM is a dry-mix, polymer-modified adhesive and base coat requiring only water for mixing.

Features:

- Pre-blended & polymer modified; just add water, mix, and use
- Long open time
- Non-sag, non-slump performance
- Excellent resistance to water penetration and efflorescence
- Good for small repairs or applications; mix only what you need

TENON®



Adhesive Base Coat PM

Uses

- Adhesive to adhere expanded polystyrene foam board that shapes to concrete, masonry surfaces (cement boards confirming with ASTM C1325 [Type A Exterior]), CMU block, glass-mat sheathing, and exterior-grade plywood
 - Use as an adhesive with EIFS/EPS to EPS
 - Use as an adhesive with EPS drainage board
 - Use as base coat for reinforcing mesh embedment
- Interior or exterior
- Horizontal and vertical applications

Approximate Coverage per 50 lb. (22.7 kg) bag	Sq. Ft.	m²
Mesh Embedment	50 - 85	4.6 - 7.9
³ / ₆ " x ³ / ₆ " x ³ / ₇ " Square Notched Trowel (10 x 10 x 10 mm)	80 - 85	7.4 - 7.9
¹ / ₂ " x ¹ / ₂ " x ¹ / ₂ " Square Notched Trowel (13 x 13 x 13 mm)	50 - 55	4.6 - 5.1
Ribbon or Dab	40 - 50	3.7 - 4.6

*Coverage rates vary depending on porosity of substrates and application techniques



For professional use only.

It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use. For technical assistance, please contact TCC Materials. To acquire technical and safety literature, please visit our website.



TCC Materials 2025 Centre Pointe Blvd Mendota Heights, MN 55120 Phone: 651.688.9116 Email: info@tccmaterials.com Web: tccmaterials.com

Available In:

Tenon® Adhesive Base Coat PM is available in a gray color in a 50 lb. bag. Approximately 40-85 sq. ft. (3.7-7.9 m²) of adhered veneer.